

# SAFETY DATA SHEET Pirtek Hydraulic Oil 46

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

Product name Pirtek Hydraulic Oil 46

Product number P8060

Internal identification GHS22746

**REACH registration number** n/a Mixture

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Hydraulic oil.

No specific uses advised against are identified. Uses advised against

# 1.3. Details of the supplier of the safety data sheet

Supplier Pirtek UK Ltd

> 199 The Vale Acton London **W37QS**

Tel: 0208 749 8444 Fax: 0208 749 8333 info@pirtek.co.uk

# 1.4. Emergency telephone number

**Emergency telephone** Pirtek UK Ltd Emergency Tel: 0800 382 438

Mon - Fri 9am - 5pm

# SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified Health hazards Not Classified **Environmental hazards** Not Classified

Classification (67/548/EEC or Not classified

1999/45/EC)

2.2. Label elements

Hazard statements NC Not Classified

Supplemental label

information

EUH210 Safety data sheet available on request.

# 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Distillates (petroleum) solvent-dewaxed heavy paraffinic

60-100%

CAS number: 64742-54-7 EC number: 265-157-1 REACH registration number: 01-

2119484627-25-XXXX

A petroleum product. DMSO extract < 3 % weight (IP 346)

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**Composition comments** Other ingredients determined not to be hazardous up to 100%.

#### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

**General information** Get medical attention if any discomfort continues.

**Inhalation** If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Get medical attention if any

discomfort continues.

**Ingestion** Get medical attention if any discomfort continues. Do not induce vomiting.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if any discomfort continues.

# 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation** Upper respiratory irritation.

Ingestion The product contains mineral oil, which if aspirated into the lungs through vomiting after

ingestion, may result in chemical pneumonia.

**Skin contact** Prolonged contact may cause redness, irritation and dry skin.

**Eye contact** Irritation of eyes and mucous membranes.

# 4.3. Indication of any immediate medical attention and special treatment needed

#### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

media

# 5.2. Special hazards arising from the substance or mixture

Specific hazards Heat from fire could result in drums bursting

Hazardous combustion

Protection against nuisance dust must be used when the airborne concentration exceeds 10

products

mg/m3. Oxides of carbon. Oxides of nitrogen.

# Pirtek Hydraulic Oil 46

#### 5.3. Advice for firefighters

Protective actions during

firefighting

Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment Wear self-contained breathing apparatus.

for firefighters

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8. Take care as floors and other surfaces may become

slippery. Keep unnecessary and unprotected personnel away from the spillage.

#### 6.2. Environmental precautions

**Environmental precautions** The product is insoluble in water and will spread on the water surface. Avoid the spillage or

runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other

suitable non-combustible material.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up In case of spillage on water prevent the spread by use of suitable barrier equipment Contain

and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Residues and empty containers should

be taken care of as hazardous waste according to local and national provisions.

# 6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. For waste disposal, see Section 13.

# SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

# SECTION 8: Exposure controls/Personal protection

# 8.1. Control parameters

#### Occupational exposure limits

#### Distillates (petroleum) solvent-dewaxed heavy paraffinic

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

Short-term exposure limit (15-minute): ACGIH 10 mg/m<sup>3</sup>

ACGIH = American Conference of Governmental Industrial Hygienists.

2-ethylhexyl zinc dithiophosphate (CAS: 4259-15-8)

**DNEL** Workers - Dermal; systemic effects: 0.14 mg/kg/day

Workers - Inhalation; systemic effects: 0.422 ppm

Workers - Inhalation; Long term systemic effects: 0.07 ppm

Workers - Dermal; local effects: 0.09 mg/cm<sup>2</sup> Workers - Inhalation; local effects: 0.42 ppm

Workers - Inhalation; Long term systemic effects: 0.21 ppm Workers - Dermal; Long term systemic effects: 0.09 mg/cm²

Workers - Dermal; Long term systemic effects:

PNEC - Fresh water; 0.004 mg/l

- Soil; 0.0548 mg/kg

- Sediment (Freshwater); 0.0701 mg/kg

- marine water; 0.0046 mg/l

- Sediment (Marinewater); 0.00701 mg/kg

- STP; 3.8 mg/l - Air; 7.1 mg/m<sup>3</sup>

# benzenesulfonic acid, mono-C16-24-alkyl derivs. (CAS: 70024-69-0)

**DNEL** Workers - Dermal; Long term systemic effects: 3.33 mg/kg

Workers - Inhalation; Long term systemic effects: 0.66 mg/m<sup>3</sup>

Consumer - Dermal; Long term systemic effects:

Consumer - Inhalation; Long term systemic effects: 0.33 mg/m<sup>3</sup>

Consumer - Oral; Long term systemic effects:

PNEC - Fresh water; 1 mg/l

- Soil; 868700000 mg/kg

- Sediment (Freshwater); 723500000 mg/kg

- STP; 100 mg/l

- marine water; 1 mg/l

- Intermittent release; 10 mg/l

- Sediment (Marinewater); 723500000 mg/kg

# 8.2. Exposure controls

#### Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield

Hand protection

The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Wash promptly with soap and water if skin becomes contaminated.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

Thermal hazards

Not anticipated under normal conditions of use. The product is combustible if heated excessively and an ignition source is applied.

# SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

**Appearance** Liquid. Colour Yellow. Odour Oil-like.

Odour threshold Not known.

Melting point -24°C Pour point

>320°C @ 101.3 kPa Initial boiling point and range

Flash point 208°C Pensky-Martens closed cup.

**Evaporation rate** Not relevant. Upper/lower flammability or

explosive limits

Not known.

Other flammability Product is not flammable but on excessive heating may become combustible.

0.876 @ 15°C Relative density

Solubility(ies) Insoluble in water. Soluble in the following materials: Organic solvents.

Partition coefficient Not determined. log Kow >7 Typical of mineral oil.

**Auto-ignition temperature** No specific test data are available.

**Decomposition Temperature** Not determined. 46 cSt @ 40°C Viscosity

**Explosive properties** Not considered to be explosive.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria

for classification as oxidising.

9.2. Other information

Volatile organic compound The product is a complex mixture, the majority of which would not be classed as a VOC.

However it cannot be discounted that trace or low levels of VOCs may be present.

# SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

# Pirtek Hydraulic Oil 46

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

Oxides of carbon. Oxides of nitrogen.

products

#### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) The product is unlikely to present any significant inhalation hazard at ambient temperatures

and under normal conditions of use.

Serious eye damage/irritation

Serious eye damage/irritation May cause mild, short lasting discomfort to eyes.

Respiratory sensitisation

Respiratory sensitisation Repeated exposure to oil mists may cause respiratory damage. There is no evidence that the

product can cause respiratory hypersensitivity.

Skin sensitisation

**Skin sensitisation**Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity This product contains mineral oils which are considered to be severely refined and not

considered to be carcinogenic under IARC. All of the oils in this product have been

demonstrated to contain less than 3% extractables by the IP346 test

Reproductive toxicity

Reproductive toxicity - fertility No data available to suggest the product will cause reproductive toxicity.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Although not classified, the product contains mineral oil. If aspirated into the lungs e.g.

through vomiting after ingestion, admit to hospital immediately.

General information This product has low toxicity. Only large quantities are likely to have adverse effects on

human health.

**Inhalation** Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at

ambient temperature.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin contact Skin irritation should not occur when used as recommended. Repeated exposure may cause

skin dryness or cracking.

# Pirtek Hydraulic Oil 46

**Eye contact** May cause temporary eye irritation.

Acute and chronic health hazards

 $\label{prolonged} \mbox{Prolonged or repeated contact with used oil may cause serious skin diseases, such as}$ 

dermatitis and skin cancer.

# Pirtek Hydraulic Oil 46

# SECTION 12: Ecological information

**Ecotoxicity** Based on available data the classification criteria are not met. Not regarded as dangerous for

the environment.

12.1. Toxicity

**Toxicity** Based on available data the classification criteria are not met. Not considered toxic to fish.

Acute aquatic toxicity

Acute toxicity - aquatic

Based on available data the classification criteria are not met.

invertebrates

12.2. Persistence and degradability

Stability (hydrolysis) The product is based on highly refined mineral oils that are considered stable to hydrolysis.

Biodegradation The product is not considered readily biodegradable, albeit the major constituents are

expected to ultimately biodegrade.

Biological oxygen demand Not determined.

Chemical oxygen demand Not determined.

12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient Not determined. log Kow >7 Typical of mineral oil.

12.4. Mobility in soil

Mobility The product is non-volatile. The product is insoluble in water and will spread on the water

surface.

Henry's law constant Not determined.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

# SECTION 13: Disposal considerations

# 13.1. Waste treatment methods

**Disposal methods** Dispose of waste via a licensed waste disposal contractor.

Waste class European Waste Catalogue (EWC) = 13 01 13\* (other hydraulic oils)

# SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

# 14.3. Transport hazard class(es)

No transport warning sign required.

#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

# Environmentally hazardous substance/marine pollutant

No

# 14.6. Special precautions for user

Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

#### SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

Control of Substances Hazardous to Health Regulations 2002 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EH40/2005 Workplace exposure limits.

**GB CLP Regulation** 

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 [UK REACH]

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Guidance Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

# 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

# Inventories

# Canada - DSL/NDSL

All the ingredients are listed or exempt.

# US - TSCA

All the ingredients are listed or exempt.

# Australia - AICS

All the ingredients are listed or exempt.

# Korea - KECI

All the ingredients are listed or exempt.

#### China - IECSC

All the ingredients are listed or exempt.

# Pirtek Hydraulic Oil 46

#### Philippines - PICCS

All the ingredients are listed or exempt.

#### New Zealand - NZIOC

All the ingredients are listed or exempt.

#### SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

CAS: Chemical Abstracts Service.

DNEL: Derived No Effect Level.

GHS: Globally Harmonized System.

IATA: International Air Transport Association.

IMDG: International Maritime Dangerous Goods.

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

(EC) No 1907/2006.

vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations and acronyms

Acute Tox. = Acute toxicity

Aquatic Acute = Hazardous to the aquatic environment (acute)

Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Asp. Tox. = Aspiration hazard Carc. = Carcinogenicity

Eye Dam. = Serious eye damage

Eye Irrit. = Eye irritation
Flam. Gas = Flammable gas
Flam. Liq. = Flammable liquid
Met. Corr. = Corrosive to metals
Repr. = Reproductive toxicity

Resp. Sens. = Respiratory sensitisation

Skin Corr. = Skin corrosion Skin Irrit. = Skin irritation Skin Sens. = Skin sensitisation

STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure

**Revision comments** NOTE: Lines within the margin indicate significant changes from the previous revision.

**Issued by** Regulatory Affairs

Revision date 02/06/2021

Revision 2

Supersedes date 29/03/2016

SDS number 22746

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.